

File: JPAB

Dec 17, 1985

PUB-NO: JP360255797A

DOCUMENT-IDENTIFIER: JP 60255797 A

TITLE: METHOD OF SELECTIVE DEPROTECTION OF PROTECTING GROUP OF ACETAL GROUP

PUBN-DATE: December 17, 1985

INVENTOR-INFORMATION:

NAME

COUNTRY

SHIBAZAKI, MASAKATSU

OGAWA, YUJI

US-CL-CURRENT: 556/449

INT-CL (IPC): C07F 7/18; C07B 61/00; C07C 177/00; C07D 205/08

ABSTRACT:

PURPOSE: To deprotect selectively only a protecting group of acetal type, by heat-treating a compound containing a protecting group of acetal type and a protecting group of silyl ether type in the molecule.

CONSTITUTION: A compound (e.g., 1-tetrahydropyranyloxy-10-t-butyldimethylsilyloxydecane, etc.) containing one or more protecting group of acetal type (e.g., tetrahydropyranyl group, etc.) and a protecting group of silyl ether type (e.g., t-butyldimethylsilyl group, etc. in the molecule is heated preferably in a solvent (e.g., toluene, etc.) at 100~250°C, to give a compound (e.g., 1-t-butyldimethylsilyloxy-10-decanol, etc.) wherein the protecting group of acetal type is selectively deprotected.

COPYRIGHT: (C)1985,JPO&Japio

DERWENT-ACC-NO: 1986-033342
DERWENT-WEEK: 198605
COPYRIGHT 2004 DERWENT INFORMATION LTD

TITLE: Protective group selective removal - by heating cpd. with acetal and silyl
gps. to remove acetal gp.

PRIORITY-DATA: 1984JP-0108607 (May 30, 1984)

Search Selected

Search ALL

Clear

PATENT-FAMILY:

	PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
<input type="checkbox"/>	<u>JP 60255797 A</u>	December 17, 1985		006	
<input type="checkbox"/>	<u>JP 91004558 B</u>	January 23, 1991		000	

INT-CL (IPC): C07B 61/00; C07C 177/00; C07D 205/08; C07F 7/18

ABSTRACTED-PUB-NO: JP 60255797A

BASIC-ABSTRACT:

Cpd. which has more than one kind of acetal type protective radical and silyl type protective radical in molecule is heated and acetal type protective radical is selectively removed.

Acetal type protective radical used is e.g. tetrahydropyranyl, 1-ethoxyethyl, methoxymethyl, methylthiomethyl, benzyloxymethyl, t-butoxymethyl, 2-methoxyethoxymethyl, 2,2,2-trichloroethoxymethyl, bis(2-chloroethoxy)methyl, 2-(trimethylsilyl)ethoxymethyl, 3-bromotetrahydropyranyl, tetrahydrothiopyranyl, 4-methoxy-tetrahydropyranyl, tetrahydrofuranlyl, 1-methyl-1-methoxyethyl.

Silylether type protective radical is e.g. t-butyldimethylsilyl triethylsilyl, tribenzylsilyl, (triphenylmethyl) dimethylsilyl, t-butyldiphenylsilyl, methyl-diisopropylsilyl, methyl-di-t-butylsilyl, triphenylsilyl, trimethylsilyl.

Heat treatment is necessary and pref. reaction temp. is 100-250 deg.C. This reaction is pref. in organic solvents e.g. benzene, toluene, xylene, hexane, acetonitrile, t-butyl alcohol, t-amyl alcohol.

USE - For protection of acetal radical.